



The PC-HD is a robust plate conveyor suitable for use in all plate line installations. The steel rollers make it ideal for connection to the exit of a plate baking oven.

Features include:

- Variable speed rollers operated by infeed and exit sensors
- Adjustable transfer height to suit most plateline equipment
- Lockable wheels can be added (replaces feet) allowing the conveyor to be moved for easier access to other plateline equipment



PC-HD | STRAIGHT CONVEYOR

| PC-HD SPECIFICATIONS | | | | |
|-----------------------------|---|----------------|-----------------|-----------------|
| | PC125-HD | | PC165-HD | |
| MODEL / LENGTH (mm) | 1000 | 1600 | 1750 | 2400 |
| PART No. | 0450A200 | 0450A215 | 0450A216 | 0450A218 |
| MAXIMUM PLATE WIDTH | 1250mm (49.2") | | 1650mm (65.0") | |
| MAXIMUM PLATE LENGTH | 1000mm (39.4") | 1600mm (63.0") | 1750mm (68.9") | 2400mm (94.57") |
| MACHINE DIMENSIONS | | | | |
| LENGTH | 1050mm (41.3") | 1634mm (64.3") | 1780mm (70.1") | 2437mm (95.9") |
| WIDTH | 1373mm (54.0") | | 1773mm (69.8") | |
| PLATE INPUT HEIGHT | 810-1000mm (31.89-39.4") | | | |
| TRANSPORT SPEED | Variable | | | |
| ELECTRICAL SUPPLY | 1Ph + N + PE/GND (2W + GND), 230 VAC, 3A, 50/60Hz | | | |
| NOISE LEVEL | <60dB | | | |
| APPROVALS | Complies to CE standards | | | |

HEIGHTS (UK) LTD. maintains a policy of continuous product improvement and reserves the right to change specification without notice

HEIGHTS (UK) LTD.
Wainstalls, Halifax, West Yorkshire
HX2 7TJ, United Kingdom
Tel.: +44 (0)1422 240914
Fax: +44 (0)1422 240589
Email: info@heights-uk.com
Web: www.heights.com

HEIGHTS USA INC.
1445 Lower Ferry Road, Ewing
Trenton, New Jersey, USA
Tel.: +1 609 530 1300
Fax: +1 609 530 9430
Email: info@heights-usa.com
Web: www.heights-usa.com

PC-HD

